

Vantage 15E0-W Workstation

Flexible, Scalable, and Secure



Intel® W790 (LGA 4677) CEB workstation motherboard, PCIe 5.0 x16, M.2, 10G and 2.5G LAN, Server-grade Remote Management, 12+1+1 power stages, front and Rear USB 3.2 Gen 2x2 Type-C®

Key Specifications:

Intel® LGA 4677 socket: Ready for Intel Xeon® W-3400 & W-2400 processors

CPU and memory overclocking: Supports for up to 2TB of ECC R-DIMM DDR5 memory (2DPC)

Ultrafast connectivity: 5 PCIe 5.0 x16 slots, 10G & 2.5G LAN, 2 M.2, front and rear USB 3.2 Gen 2x2 Type-C® and 3 SlimSAS

Server-grade IPMI remote management: Hardware and software-level with IPMI expansion card support, plus a real-time monitoring and management software Control Center Express

Robust power and thermal design: 12+1+1 power stages, 8-pin PCIe power connector, Massive VRM, chipset and M.2 heatsinks and M.2 backplate

Trusted stability: Highly compatible with the latest technologies with solid QVL list and tested for 24/7 operation, validated for extensive compatibility

Technical details

Vantageo 15E0-W Details

Processor	Intel® Socket LGA4677 for Xeon® W-3400 and W-2400 Series Processors* Supports Intel® Turbo Boost Max Technology 3.0
CPU	Intel® W790 Chipset
Memory	8 x DIMM slots, Max. 2048GB, DDR5 6800(OC)/6600(OC)/6400(OC)/6200(OC)/6000(OC)/5800(OC)/5600(OC)/5400(OC)/5200(OC)/5000(OC)/4800 ECC Registered Memory* Quad Channel Memory Architecture Supports Intel® Extreme Memory Profile (XMP) * Supported memory types, data rate (speed), and number of DRAM modules vary depending on the CPU and memory
Expansion Slots	Intel® Xeon W-3400 and W-2400 Series Processors 5 x PCIe 5.0 x16 slot(s) (supports x16, x16, x16, x0/x8, x16/x8 modes) Please check the PCIe bifurcation table on the support To ensure compatibility of the device installed, peripherals.
Storage	Total supports 2 x M.2 slots, 4 x SATA 6Gb/s ports and 3 x SlimSAS ports* Intel® W790 Chipset** M.2_1 slot (Key M), type 2242/2260/2280/22110 (supports PCIe 4.0 x4 mode) M.2_2 slot (Key M), type 2280 (supports PCIe 4.0 x4 mode) SlimSAS_1 slot supports PCIe 3.0 x4 mode NVMe device SlimSAS_2 slot supports PCIe 4.0 x4 mode or up to 4 SATA devices via a transfer cable. The cable is purchased separately. SlimSAS_3 slot supports PCIe 4.0 x4 mode NVMe device 4 x SATA 6Gb/s ports* * Supports Intel® Virtual RAID on CPU (Intel® VROC) and Intel Volume Management Device (Intel®VMD) ** Intel® VROC Technology supports PCIe RAID 0/1/5/10, SATA RAID 0/1/5/10. VROC HW_Key is purchased separately.
Ethernet	1 x Marvell® AQtion 10Gb Ethernet 1 x Intel® 2.5Gb Ethernet
USB	Rear USB (Total 13 ports) 1 x USB 3.2 Gen 2x2 port(s) (1 x USB Type-C®) 4 x USB 3.2 Gen 2 port(s) (4 x Type-A) 8 x USB 2.0 port(s) (8 x Type-A) Front USB (Total 7 ports) 1 x USB 3.2 Gen 2x2 (supports USB Type-C®) 1 x USB 3.2 Gen 1 header(s) support(s) 2 additional USB 3.2 Gen 1 ports 2 x USB 2.0 header(s) support(s) 4 additional USB 2.0 ports
Audio	Realtek S1220A 7.1 Surround Sound High Definition Audio CODEC* - Impedance sense for front and rear headphone outputs - Internal audio Amplifier to enhance the highest quality sound for headphone and speakers - Supports: Jack-detection, Multi-streaming, Front Panel Jack-retasking - High quality 120 dB SNR stereo playback output and 113 dB SNR recording input (Line-in) - Supports up to 32-Bit/192 kHz playback*

Technical details

Vantageo 15E0-W Details

	Audio Features - Power pre-regulator reduces power input noise to ensure consistent performance - Rear optical S/PDIF out port - Premium audio capacitors - Dedicated audio PCB layers - Unique de-pop circuit * Due to limitations in HDA bandwidth, 32-Bit/192 kHz is not supported for 7.1 Surround Sound audio.
Back Panel I/O Ports	1 x USB 3.2 Gen 2x2 port(s) (1 x USB Type-C®) 4 x USB 3.2 Gen 2 port(s) (4 x Type-A) 8 x USB 2.0 port(s) (8 x Type-A) 1 x Marvell® AQtion 10Gb Ethernet port 1 x Intel® 2.5Gb Ethernet port 5 x Audio jacks 1 x Optical S/PDIF out port 1 x BIOS FlashBack™ button 1 x Clear CMOS button
Internal I/O Connectors	Fan and Cooling related 1 x 4-pin CPU Fan header(s) 1 x 4-pin CPU OPT Fan header(s) 5 x 4-pin Chassis Fan header(s) 1 x W_PUMP+ header(s) Power related 2 x 24-pin Main Power connector 4 x 8-pin +12V Power connector 1 x 8-pin PCIe Power connector Storage related 2 x M.2 slots (Key M) 3 x SlimSAS slots 4 x SATA 6Gb/s ports USB 1 x USB 3.2 Gen 2x2 connector (support(s) USB Type-C®) 1 x USB 3.2 Gen 1 header(s) support(s) 2 additional USB 3.2 Gen 1 ports 2 x USB 2.0 header(s) support(s) 4 additional USB 2.0 ports Miscellaneous 1 x BMC header 1 x COM Port header 1 x FlexKey button 1 x Front Panel Audio header (AAFP) 1 x LN2 Mode jumper 1 x ReTry button 1 x Start button 1 x SPI TPM header (14-1pin) 1 x 20-3 pin System Panel header with Chassis intrude function 1 x Thermal Sensor header 1 x VROC Key header

Technical details

Vantageo 15E0-W Details

Special Features

- Extreme OC Kit
- FlexKey button
 - ReTry button
 - Start button
- 5X PROTECTION III
- DIGI+ VRM (- Digital power design with DrMOS)
 - ESD Guards
 - LANGuard
 - Overvoltage Protection
 - Safeslot
 - Stainless-Steel Back I/O
- Q-Design
- M.2 Q-Latch
 - Q-Code
 - Q-Connector
 - Q-DIMM
 - Q-LED (CPU [red], DRAM [yellow], VGA [white], Boot Device [yellow green])
 - Q-Slot
- Thermal Solution
- M.2 heatsink backplate
 - M.2 heatsink
 - VRM heatsink design
- EZ DIY
- BIOS FlashBack™ button
 - BIOS FlashBack™ LED
 - Clear CMOS button
 - ProCool II
 - Pre-mounted I/O shield
 - SafeSlot
 - SafeDIMM
- Bespoke Motherboard Design & Business Focused Features
- 24/7 Reliability
 - Overcurrent Protection

Software Features

- Exclusive Software
- Armoury Crate
- Fan Xpert 4
- AI Suite 3
- TPU
 - DIGI+ VRM
 - Turbo app
 - PC Cleaner
- CPU-Z
- IT Management software supported
- Control Center Express(ACCE)

Technical details

Vantageo 15E0-W Details

	Adobe Creative Cloud (Free Trial) Norton 360 Deluxe (60 Days Free Trial) WinRAR UEFI BIOS EZ DIY - CrashFree BIOS 3 - Start EzFlash FlexKey
BIOS	512 Mb Flash ROM, UEFI AMI BIOS
Manageability	WOL by PME, PXE (UEFI mode)
Accessories	Cables 2 x SATA 6Gb/s cables Miscellaneous 1 x Q-connector 1 x M.2 Rubber Package(s) 1 x M.2 backplate Rubber Package(s) 1 x CPU guard for LGA 4677 E1A 1 x CPU guard for LGA 4677 E1B Documentation 1 x ACC Express Activation Key Card 1 x User guide
Operating System	Windows® 11, Windows® 10 64-bit
Power supplies	Power supplies
Form Factor	CEB Form Factor 12 inch x 10.5 inch (30.5 cm x 26.67 cm)

Recommended support

24x7 - 4 hours Response, Next Business Day Call to Resolution CTR

24x7 - 4 hours Response, 24 Hours Call to Resolution CTR

24x7 - 4 Hours Response, 6 Hours Call to Resolution CTR

Default support Next Business Day Consulting and deployment offerings are also available. Contact Vantageo representative for the more information.