

Vantageo 25HD-C

Flexible, Scalable, and Secure



2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors Dual Socket LGA-3647 (Socket P) supported, CPU TDP support Up to 205W TDP, 2 UPI up to 10.4 GT/s

Overview

The Vantageo 25HD-C is a high-performance, dual-socket server motherboard designed by Vantageo, engineered to support Intel's Xeon Scalable processors (1st and 2nd generation). It's tailored for use in demanding enterprise environments, offering robust processing power, extensive memory capacity, and versatile expansion options. The motherboard is ideal for tasks such as virtualization, data analytics, and large-scale database management.

Features

- Intel® C622
- Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM DDR4-2933MHzOr 2TB Intel® PMem, DDR4-2666MHz, in 16 DIMM slots;Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)
- 4 PCI-E 3.0 x16, 2 PCI-E 3.0 x8, 2 PCI-E 3.0 NVMe x4 Internal Port(s) M.2 Interface: PCI-E 3.0 x4 M.2 Form Factor: 2260, 2280, 22110 M.2 Key: M-Key
- 1 VGA port
- Intel® C622 controller for 14 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- Dual LAN with 10GBase-T with Intel® X722 + X557

- 90° Rotatable HDD Cage
- Whisper-Quiet (<21dB)
- Kensington Lock Support
- Front I/O Ports: 2x Audio (HD/AC97) & 2xUSB 3.0 & 2x USB 2.0
- 900W Gold Level Certified High-Efficiency Power Supply
- 1x Optional Front 12cm (1850 RPM) PWM Fan

Vantageo 25HD-C

- Mid-Tower Chassis Supports Micro-ATX Motherboard, Sizes □ E-ATX/ATX/Micro ATX
- 2x 5.25" External HDD Drive Bays & 4x 3.5" Internal HDD Drive Bays
- 1x Rear 12cm (1850 RPM) PWM Fan

Dual Socket:

Supports Intel Xeon Scalable processors with up to 28 cores per processor, providing significant computational power for intensive workloads.

Memory:

Features 16 DDR4 DIMM slots, capable of accommodating up to 4TB of ECC Registered Memory, ensuring stability and performance in memory-intensive applications.

Expansion

Offers a variety of PCIe slots, including four PCIe 3.0 x16 and three PCIe 3.0 x8 slots, allowing for high-bandwidth peripherals, including GPUs and storage controllers.

Networking:

Integrated dual 10GbE LAN ports via the Intel X550 controller, providing high-speed network connectivity suitable for data-heavy operations.

More Storage

Includes 10 SATA3 ports for traditional storage solutions and 2 NVMe ports for high-speed SSDs, offering flexibility in storage configurations.

Management:


Comes with integrated IPMI 2.0 and a dedicated management LAN port, enabling remote monitoring and management, crucial for maintaining server uptime.

Form Factor:

E-ATX, fitting into standard server chassis, making it versatile for various data center environments.

The Vantageo 25HD-C motherboard has onboard networking capabilities provided by dual 10 Gigabit Ethernet (10GbE) LAN ports. These ports are powered by the Intel X550 controller, which supports high-speed data transfer suitable for demanding network environments. This makes the motherboard well-suited for data-intensive tasks, such as server operations, virtualization, and high-performance computing.

The Vantageo 25HD-C is an ideal choice for businesses and organizations seeking a powerful and reliable server motherboard to handle large-scale, mission-critical applications.



Vantageo 25HD-C	
Features	Technical Specification
CPU	2nd Gen Intel® Xeon® Scalable Processors and Intel® Xeon® Scalable Processors Dual Socket LGA-3647 (Socket P)supported, CPU TDP support Up to 205W TDP, 2 UPI up to 10.4 GT/s
Form Factor	Mid Tower Chassis
Dimensions	12" x 13" (30.48cm x 33.02cm)
Memory Capacity	Up to 4TB 3DS ECC RDIMM, DDR4- 2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz Or 2TB DCPMM, DDR4-2666MHz, in 16 DIMM slots; Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only)
Memory Voltage	1.2V
Memory Type	2933/2666/2400/2133MHz ECC 4 RDIMM, LRDIMM
DIMM Sizes	• RDIMM: 64GB • LRDIMM: 128GB • 3DS LRDIMM: 256GB
PCI - Express	4 PCI-E 3.0 x16 2 PCI-E 3.0 x8
M.2	M.2 Interface: PCI-E 3.0 x4 Form Factor: 2260, 2280, 22110 Key: M-Key
Chipset	Intel® C622 chipset
Network Controllers	Dual LAN with 10GBase-T with Intel® X722 + X557
IPMI	ASPEED AST2500
SATA	Intel® C622 controller for 14 SATA3 (6 Gbps) ports; RAID 0,1,5,10
Graphics	ASPEED AST2500 BMC
USB	4 USB 2.0 ports (2 rear + 2 via headers) 5 USB 3.2 Gen1 ports (2 rear + 2 via headers + 1 Type A)
VGA	1 VGA port
TPM	1 TPM Header
Serial Port / Header	2 COM Ports (1 rear, 1 header)
BIOS Type	AMI UEFI
Software	Intel® Node Manager, IPMI2.0, KVM with dedicated LAN, SPM, SSM, SUM, SuperDoctorSoftware ® 5, Watchdog
Environmental Spec.	Operating Temperature: 10°C - 35°C (50°F - 95°F) Non-operating Temperature: -40°C - 70°C (-40°F - 158°F) Operating Relative Humidity: 8% to 90% (non-condensing) Non-operating Relative Humidity: 5% to 95% (non-condensing)
Voltage	+12V, +3.3V, +5V, +5V standby, 3.3V standby, Monitors CPU voltages
FAN	8x 4-pin fan headers (up to 8 fans), PWM fan speed control
LED	CPU / System Overheat LED, UID/Remote UID, BMC/IPMI Heartbeat LED, Power LED
Temperature	CPU thermal trip support, Monitoring for CPU and chassis environment, PECI
Other Features	ACPI power management, ATX Power connector, Chassis intrusion detection, Chassis intrusion header, Control of power-on for recovery from AC power loss, CPU thermal trip support for processor protection, NCSI header, Node Manager Support, RoHS, SDDC, UID

Disclaimer: Technical data is subject to modification and delivery subject to availability. . Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

Vantageo 25HD-C

Part No	Description
VT 25HD-C	Vantageo 25HD-C
VT 25HD-C-G226R	Intel® Xeon® Gold 6226R Processor 22M Cache, 2.90 GHz
VT 25HD-C-0211	Intel C622 Chipset
VT 25HD-C-20B3	32GB DDR4 2933 MHz
VT 25HD-C-3042	1TB NVME SSD
VT 25HD-C-4192	2TB SATA HDD
VT 25HD-C-0435	Mid Tower
VT 25HD-C-G015	900W Gold Level Certified High-Efficiency Power Supply
VT 25HD-C-7111	Dual LAN with 10GBase-T with Intel® X722 + X557
VT 25HD-C-04A0	CPU Heat Sink
VT 25HD-C-T10008	NVIDIA T1000 8GB
VT 25HD-C-KBM	USB Key Board & Mouse

Disclaimer: Technical data is subject to modification and delivery subject to availability. . Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.